



www.kidsflysafe.com



Instructional Safety Card

The following steps depict how to properly install and remove the CARES restraint. This restraint is not approved for use in any manner other than that depicted in these instructions.

Installation Limitations

The following paragraphs describe the installation limitations for the CARES restraint.

A. EMERGENCY EXIT ROW: This device may not be used in an emergency exit row or in any other location where a child is restricted from occupying the seat.

B. SEAT ORIENTATION: Use only in a forward-facing seat. Do not use this device in a side-facing seat.

C. OCCUPANT SIZE: The Type III child restraint is designed for use only by children who weigh 22-44 pounds (10-20 kilograms), whose height is 40 inches (101.6 centimeters) or less, and who can sit upright unassisted.

D. INFLATABLE RESTRAINTS: It is prohibited to install and use a child safety restraint behind any wall or seat back that has an inflatable airbag and on any seat that has an inflatable restraint system.

E. TRAY TABLES: On seats where the seat back's tray table is stowed flat against the sides of the seat back, install CARES under the tray table. On seats where the side of the seat back's tray table is stowed into a recessed area, install CARES over the tray table.

F. AUTOMOBILE USAGE: Do not use this device in an automobile. The CARES child restraint device has not been certified for use in automobiles.

G. THREE-POINT SHOULDER STRAP RESTRAINT:

Use only the airplane passenger seat lap-belt to attach this child restraint. This child restraint is not designed to be used with a shoulder strap or any other tether strap attached to the seat or airplane.

H. The conditions and test required by FAA letter dated December 19, 2005, "CRS Requirements," are minimum-standard performance standards.

I. Check with your carrier for additional requirements. Airline instructions/restrictions may vary.

WARNINGS

DEATH OR SERIOUS INJURY MAY OCCUR if this restraint is not installed properly. Use only in a forward-facing seat. Attach this child restraint with the passenger seat lap-belt. Adjust this child restraint's belts snugly around your child. Follow ALL instructions on this child restraint and in the manufacturer's written instructions.

The CARES restraint may be carried on board an aircraft and installed by the passenger according to the amended operating rules under Title 14 CFR 91.107, §121.311, §125.211 and §135.128.

For information on traveling safely with children, go to the "Flying with Children" section of "Travelers" at www.faa.gov, or visit www.kidsflysafe.com.



Instructions for Most Standard Airplane Seats

On seats where the tray table is stowed flat against the seat back (not recessed), as shown in Figure 1, the CARES restraint must be installed under the tray table and can be used for the duration of the flight.

1 Place your child in the airplane seat he/she will be traveling in. Lower the seat back's tray table that is behind the child's seat. Then slide the CARES' large red loop over the seat back, as shown in Step 1.

The red loop should have the yellow warning and installation labels facing forward.

2 Adjust the red loop by pulling the loose end of the red strap in a direction away from the seat back, as shown in Step 2, until the loop is slightly snug but not tight.

Adjust the height of the red loop so that it is at or just above the child's shoulders. Securely tighten the red loop around the seat by pulling once again on the end of the red strap. Move the black plastic slide to smooth out excess red belting.

If the red loop is too tight, you can loosen it by pulling the short black pull strap (located on the silver metal adjuster) in the direction opposite that used to tighten the red loop.

Re-stow the tray table behind the child's seat. The tray table will cover the red loop.

3 Verify that the shoulder straps are not twisted.

Loosen and lengthen each shoulder strap by pushing up on the black metal adjuster's gray button and then pulling down on the small black loops at the end of each shoulder strap, as shown in Step 3.


Do not connect the chest clip until the end of Step 4.

4 Place the connector and buckle of the airplane seat lap-belt through the small black loops at the end of each shoulder strap, as shown in Step 4. Be certain your child is sitting firmly upright in his/her seat.

Buckle the lap-belt and tighten it snugly around the child. Connect the chest clip.

5 Align the shoulder straps vertically and tighten the black shoulder adjusters by pulling down on the loose end of each black strap, as shown in Step 5. To ensure your child is properly restrained, please verify that all the straps are firmly fastened. To finish the installation, align the chest clip.

If the shoulder straps are too tight, loosen and lengthen each strap by pushing up on the black metal adjuster's gray button and then pulling down on the small black loops at the end of each strap, where the lap-belt buckle is located.



Removal Instructions

6 To free your child from the CARES restraint, release the lap-belt buckle, as shown in Step 6, and then slide the buckle and connector out of the black loops.

7 Release the chest clip, as shown in Step 7, and allow your child to exit the seat.

8 To remove the CARES restraint from the seat, release the silver metal adjuster on the red loop by moving the black plastic slide toward the silver metal adjuster and then pull on the adjuster's small black pull strap, as shown in Step 8.



Emergency Removal Instructions


Fig.2 In an emergency, you can release the lap-belt and then pull the shoulder straps and chest clip over your child's head, as shown in Figure 2.



Instructions for Select Airplane Seats

Fig.3 Seats with a recessed tray table – defined as a table that is stored in a cavity with rigid recessed sides. Install the CARES restraint's red loop over the stowed tray table, as shown in Figure 3.

Refer to Steps 2-5 above for follow-on installation. (Note: the tray table will be stowed.) The restraint is used during taxi, takeoff and landing, or during turbulent conditions when instructed by the airplane captain. If the person behind the child wishes to use their tray table, remove the restraint, lower the tray table, and reinstall CARES as previously instructed.



CARES conforms to US Patent Number 6,402,251. ©2013 Kids Fly Safe. CARES and the Kids Fly Safe Logo are trademarks of AmSafe, Inc. All rights reserved. www.kidsflysafe.com